

Product 2 Pack Acrylic Polyurethane Gloss Finish
 Revision date 18 September 2020
 Revision 2



Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	2 Pack Acrylic Polyurethane Gloss Finish
Synonyms, Trade names	No information available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Paint or paint related material. For industrial and professional use only.
Uses advised against	Any other purpose.

1.3 Details of the supplier of the safety data sheet

Supplier	Castle Paints Ltd Cloncollig Industrial Estate Tullamore Offaly R35 X993 Ireland Tel: 353 (0)579351583 info@castlepaints.ie
Contact person	

1.4 Emergency telephone number

Emergency telephone	Emergency medical information: 8am - 10pm (Seven Days) contact National Poison Center, Beaumont Hospital. Telephone: +353 (0) 18092166
----------------------------	--

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)	
Physical and chemical hazards	Flam. Liq 3 - H226
Human health	Skin Irrit.2 - H315, Eye Irrit.2A - H319, STOT RE 2 - H373, Asp. Tox - H304
Environment	Aquatic Chronic 3 - H412

2.2 Label elements

Contains	Xylene Hydrocarbons, C9 aromatics Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 2-methylpropan-1-ol
-----------------	--

Label in accordance with (EC) no. 1272/2008



Signal word	Danger
--------------------	--------

Hazard statements	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation.
--------------------------	--

H373 May cause damage to organs through prolonged or repeated exposure
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P260 Do not breathe dust/fume/ gas/mist/vapours/spray.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry chemical, foam or carbon dioxide for extinction.

EUH statements

EUH208 Contains reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

2.3 Other hazards

None known.

Section 3: Composition/identification of ingredients**3.1 Substance**

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
Xylene	CAS-No.: 1330-20-7 EC No.: 215-535-7 REACH Reg No.: 01-2119488216-32-xxxx	Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Eye Irrit.2A - H319, STOT SE 3 - H335, STOT RE 2 - H373, Asp. Tox - H304, Flam. Liq 3- H226, Aquatic Chronic 3 - H412	20-30%
Hydrocarbons, C9 aromatics	CAS-No.: EC No.: 918-668-5 REACH Reg No.: 01-2119455851-35-xxxx	STOT SE 3 - H335, STOT SE 3 - H336, Asp. Tox - H304, Flam. Liq 3- H226, Aquatic Chronic 2 - H411	15-20%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-0046		5-10%
2-butoxyethanol	CAS-No.: 111-76-2 EC No.: 203-905-0 REACH Reg No.: 01-2119475108-36-0000	Acute Tox 4 - H302, Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Eye Irrit.2A - H319	0.1-0.9%
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	CAS-No.: EC No.: 919-446-0 REACH Reg No.: 01-2119458049-33-XXXX	Aquatic Chronic 2 - H411, Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336, STOT RE 1 - H372	0.1-0.9%
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS-No.: EC No.: 915-687-0 REACH Reg No.: 01-2119491304-40-0000	Aquatic Chronic 1 - H410, Skin. Sens 1 A- H317, Aquatic Acute 1 - H400	0.1-0.9%
2-methylpropan-1-ol	CAS-No.: 78-83-1 EC No.: 201-148-0 REACH Reg No.: 01-2119484609-23-0000	Skin Irrit.2 - H315, Eye Dam. 1 - H318, Flam. Liq 3- H226, STOT SE 3 - H335, STOT SE 3 - H336	0.1-0.9%
ethylbenzene	CAS-No.: 100-41-4 EC No.: 202-849-4 REACH Reg No.: 01-2119489370-35-XXXX	Aquatic Chronic 3 - H412, Acute Tox 4 - H332, Asp. Tox - H304, Flam. Liq 2- H225, STOT RE 2 - H373	1-5%
toluene	CAS-No.: 108-88-3 EC No.: 203-625-9 REACH Reg No.: 01-2119471310-51-XXXX	Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 2- H225, Repr. 2 - H361, STOT SE 3 - H336, STOT RE 2 - H373	0.001-0.009%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Section 4: First aid measures

4.1 Description of first aid measures

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. First aid personnel must be aware of own risk during rescue.
Inhalation	If this product is inhaled and symptoms occur, move the exposed person to fresh air promptly. If breathing has stopped or the exposed person experiences difficulty in breathing, administer artificial respiration and seek immediate medical assistance.
Ingestion	If this product is ingested, remove victim immediately from source of exposure. Thoroughly rinse the mouth with water. DO NOT induce vomiting! If swallowed, seek medical advice immediately and show the container or label. If vomiting occurs, keep head low so that stomach content doesn't enter the lungs. Never give anything by mouth to an unconscious person.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash exposed area with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues after rinsing.
Eye contact	Avoid contaminating unaffected eye. Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Remove contact lenses if present and easy to do so. Continue to rinse for at least 15 minutes. Get prompt medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. May cause damage to organs through prolonged or repeated exposure.
Inhalation	Inhalation of high concentrations of vapours may cause drowsiness and dizziness.
Ingestion	May cause gastrointestinal irritation, nausea, vomiting and diarrhoea. May be fatal if swallowed and enters airways.
Skin contact	Contact with skin may cause irritation. May cause an allergic skin reaction. Avoid contact.
Eye contact	Causes serious eye irritation. May cause redness, swelling, pain and tearing.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
-------------------------------	------------------------

Section 5: Fire-fighting measures

5.1 Extinguishing media

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Dry chemical, foam or carbon dioxide.
Unsuitable extinguishing media	High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	Combustion products may include and are not limited to: Oxides of carbon. Oxides of Nitrogen.
Unusual fire & explosion hazards	The product is classified as a flammable liquid and vapour. Vapours are heavier than air and may spread near ground to sources of ignition. Do not allow to enter drains, sewers, basements and workpits, or any place where its accumulation can be dangerous.
Specific hazards	When heated and in case of fire, harmful vapours/gases may be formed. Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special fire fighting procedures	Ventilate closed spaces before entering them. Water spray should be used to cool containers. If possible, fight fire from protected position. Containers close to fire should be removed immediately or cooled with water if safe to do so. Keep up-wind to avoid fumes.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Keep unnecessary and unprotected personnel from entering. Read and follow manufacturer's recommendations.

For emergency responders

Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions**Environmental precautions**

Do not allow to enter sewers/ surface or ground water. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up**Spill clean up methods**

Wear appropriate personal protective equipment as specified in Section 8. Eliminate all sources of ignition. Ventilate and evacuate the area. Cover drains. Prevent further leakage or spillage if safe to do so.
Use non sparking tools or equipment for clean up. Absorb spillage with inert, damp, non-combustible material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

6.4 Reference to other sections**Reference to other sections**

See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.

Section 7: Handling and storage**7.1 Precautions for safe handling****Handling**

Provide good ventilation. Wear suitable personal protective equipment, as detailed in Section 8. Keep away from ignition sources. Use non sparking tools. Avoid inhalation of vapours. Avoid contact with skin and eyes.
Read and follow manufacturer's recommendations. Avoid prolonged or repeated contact. Do not wear contact lenses.

7.2 Conditions for safe storage, including any incompatibilities**Storage precautions**

Keep upright, locked up and out of reach of children. Store in closed, labelled containers in a cool, dry, well-ventilated area away from incompatible materials. Containers once opened must be carefully resealed to prevent leakage. Protect from direct sunlight. Prohibit ignition sources close to storage area. Keep away from incompatible materials (see section 10).

Storage class

Flammable liquid storage.

7.3 Specific end use(s)**Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

Usage description

Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection**8.1 Control parameters**

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
xylene	OEL	50 ppm	221 mg/m ³	100 ppm	442 mg/m ³	Mixed isomers, Sk, IOELV.
titanium dioxide	OEL		10 mg/m ³			Total inhalable dust.
titanium dioxide	OEL		4 mg/m ³			Respirable dust.
ethylbenzene	OEL	100 ppm	442 mg/m ³	200 ppm	884 mg/m ³	Sk, IOELV.
2-butoxyethanol	OEL	20 ppm	98 mg/m ³	50 ppm	246 mg/m ³	Sk, IOELV.
2-methylpropan-1-ol	OEL	50 ppm	150 mg/m ³	75 ppm	225 mg/m ³	
toluene	OEL	50 ppm	192 mg/m ³	100 ppm	384 mg/m ³	Sk, IOELV.

Ingredient comments

Ireland, Occupational Exposure Limits 2020.

8.2 Exposure Controls**Protective equipment****Engineering measures**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Where necessary use lighting and electrical equipment designed for use in atmospheres where flammable vapours are present, and which can direct static electricity by grounding equipment.

Respiratory equipment

If the respirator is the sole means of protection, use a supplied air self contained breathing apparatus operated in positive pressure mode. Use respirators and components tested and approved under appropriate government standards such as CEN (EU). Use respiratory protection as specified by an industrial hygienist or other qualified professional. Change filters frequently.

Hand protection

Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN 143 should be used, and suitable respirator cartridges as a backup to engineering controls. Multi-purpose (combination) ABEK (EN 14387) respirator cartridges. Where aerosols are in use, use self contained breathing apparatus with a type AX filter or appropriate combined filter (e.g. AX-P3).

Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Where hand contact with the product may occur use gloves approved to relevant standards (e.g. Europe: EN374.) Gloves must be inspected prior to use.

Suggested material: Viton. Polyvinyl alcohol (PVA). >8 hours (breakthrough time). Splash contact: Nitrile. Minimum layer thickness: >0.45mm. Breakthrough time: > 30 min. Consult manufacturer for specific advice on material.

Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Change gloves regularly.

Eye protection

Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).

Other protection

Wear appropriate clothing to prevent any possibility of skin contact. Fire/chemical resistant full-length overalls and boots.

Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the European norm standard EN 943.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work. Wash promptly if skin becomes contaminated.

Process conditions

Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	Viscous liquid.
Colour	Various.
Odour	Aromatic hydrocarbons.
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	No information available as testing has not been completed.
pH-Value, Diluted solution	No information available as testing has not been completed.
Melting point	No information available as testing has not been completed.
Initial boiling point and boiling	>35°C

range

Flash point	23.00 - 60.00 °C
Evaporation rate	No information available as testing has not been completed.
Flammability state	No information available as testing has not been completed.
Flammability limit - lower(%)	1.00
Flammability limit - upper(%)	9.00
Vapour pressure	No information available as testing has not been completed.
Vapour density (air=1)	No information available as testing has not been completed.
Relative density	1.0 - 1.2 g/cm ³
Bulk density	No information available as testing has not been completed.
Solubility	Not miscible.
Decomposition temperature	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	No information available as testing has not been completed.
Auto ignition temperature (°C)	No information available as testing has not been completed.
Viscosity	Viscous.
Explosive properties	Not considered to be explosive.
Oxidising properties	The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight	The product is a mixture, molecular weight data is not required.
Volatile organic compound	Cat A(j)500g/l. Max VOC: 490 g/l.
Other information	None noted.

Section 10: Stability and reactivity**10.1 Reactivity**

Reactivity	Reaction with: strong oxidising substances and acids.
-------------------	---

10.2 Chemical stability

Stability	Stable under normal temperature conditions and recommended use.
------------------	---

10.3 Possibility of hazardous reactions

Hazardous reactions	For information on hazardous reactions see section 10.1.
Hazardous polymerisation	No information available for the mixture as testing has not been completed.
Polymerisation description	No information available for the mixture as testing has not been completed.

10.4 Conditions to Avoid

Conditions to avoid	Heat, sparks, open flames, temperature extremes and direct sunlight.
----------------------------	--

10.5 Incompatible materials

Materials to avoid	Keep away from incompatibles such as oxidizing agents, acids, alkalis. Do not mix with other chemicals unless listed on directions.
---------------------------	---

10.6 Hazardous decomposition products

Hazardous decomposition products Decomposition products can include and are not limited to: Oxides of carbon. Nitrogen oxides.

Section 11: Toxicological information**11.1 Information on toxicological effects**

Toxicological information	Not classified based on available information.
Acute toxicity (Oral LD50)	No information available as testing has not been completed.
Acute toxicity (Dermal LD50)	No information available as testing has not been completed.
Acute toxicity (Inhalation LD50)	No information available as testing has not been completed.
Serious eye damage/irritation	Causes serious eye irritation.
Skin corrosion/irritation	The product is classified as a skin corrosion/irritation hazard.
Respiratory sensitisation	The product is not classified as a respiratory hazard.
Skin sensitisation	The product is not classified as a skin sensitisation hazard.
Germ cell mutagenicity	The product is not classified as a mutagen.
Carcinogenicity	The product is not classified as a carcinogen hazard.
Specific target organ toxicity - Single exposure:	
STOT - Single exposure	The product is not classified as a single exposure specific target organ toxin.
Specific target organ toxicity - Repeated exposure:	
STOT - Repeated exposure	The product is classified as a repeat exposure specific target organ toxin. May cause damage to organs through prolonged or repeated exposure.
Inhalation	Inhalation of high concentrations of vapours may cause drowsiness and dizziness.
Ingestion	May cause gastrointestinal irritation, nausea, vomiting and diarrhoea. May be fatal if swallowed and enters airways.
Skin contact	Contact with skin may cause irritation. May cause an allergic skin reaction. Avoid contact.
Eye contact	Causes serious eye irritation. May cause redness, swelling, pain and tearing.
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
Routes of entry	Eye and skin contact, ingestion or inhalation.
Target organs	Eyes, skin, digestive system, respiratory system.
Aspiration hazards:	The product is classified as an aspiration hazard.
Reproductive toxicity:	The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
xylene	4300.00mg/kg Rat		5000.00ppmV Rat 4 Hours
2-butoxyethanol	1746.00mg/kg Rat	1100.00mg/kg Rat	
2-methylpropan-1-ol	>2000.00mg/kg Rat	>2000.00mg/kg Rat	
Hydrocarbons, C9 aromatics	3492.00mg/kg Rat	>3160.00mg/kg Rat	
ethylbenzene	3500.00mg/kg Rat	15400.00mg/kg Rabbit	2180.00ppmV Rat 4 Hours

Section 12: Ecological information**12.1 Toxicity**

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.
Chronic toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.

Ecotoxicity
Eco toxicological information

Harmful to aquatic life with long lasting effects.
 Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Degradability
Biological oxygen demand
Chemical oxygen demand

No information available as testing has not been completed on the finished product.
 No information available as testing has not been completed.
 No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential
Bioaccumulation factor
Partition coefficient; n-Octanol/Water

No information available as testing has not been completed on the finished product.
 No information available as testing has not been completed.
 No information available as testing has not been completed.

12.4 Mobility in soil

Mobility

Readily absorbed in soil. Not miscible in water.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB substances.

12.6 Other adverse effects

Other adverse effects

None known.

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
2-methylpropan-1-ol	LC50 96 Hours >100.00mg/l Freshwater Fish	EC50 48 Hours >100.00mg/l Daphnia magna	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LC50 96 Hours 0.97mg/l Lepomis macrochirus (Bluegill)		
Xylene	LC50 96 Hours 13.40mg/l Pimephales promelas (Fat-head Minnow)	EC50 48 Hours >3.40mg/l Daphnia magna	
Hydrocarbons, C9 aromatics	LC50 96 Hours 9.20ppm Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 3.20ppm Daphnia magna	
ethylbenzene	LC50 96 Hours 32.00mg/l Lepomis macrochirus (Bluegill)		
toluene	LC50 96 Hours 12.60mg/l Pimephales promelas (Fat-head Minnow)	EC50 48 Hours 11.50mg/l Daphnia magna	

Section 13: Disposal considerations

Waste management

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

13.1 Waste treatment methods

Disposal methods

Dispose of waste and residues in accordance with local authority requirements, and in accordance with the European Directives on waste and hazardous waste. For waste disposal, use a licensed industrial waste disposal agent.

Section 14: Transport information

14.1 UN number

UN no. (ADR) UN1263
 UN no. (IMDG) UN1263
 UN no. (IATA) UN1263

14.2 UN proper shipping name

ADR proper shipping name	PAINT or PAINT RELATED MATERIAL
IMDG proper shipping name	PAINT or PAINT RELATED MATERIAL
IATA proper shipping name	PAINT

14.3 Transport hazard class(es)

ADR class	3
IMDG class	3
IATA class	3

Transport labels

**14.4 Packing group**

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	F-E, S-E
Emergency action code	A3 A72 A192
Hazard no. (ADR)	30
Tunnel restriction code	(D/E)

14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

Not applicable.

Section 15: Regulatory information**15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 830/2015 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Approved code of practice	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
Chemical safety assessment	No chemical safety assessment has been carried out.

Section 16: Other information

General information	This Safety Data Sheet is in accordance with REACH Annex II, (EC) No 830/2015. 2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
Revision comments	[2]Information updated. [3]Information updated. [4]Information updated. [5]Information updated. [6]Information updated. [8]Code of practice updated. Information updated. [9]Information updated. [10]Information updated. [11]Information updated. [12]Information updated. [13]Information updated. [15]Information updated.

Revision date	18 September 2020
Supersedes date	20 January 2017
Revision	2
Safety data sheet status	Approved.

Hazard statements in full

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure .
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H318	Causes serious eye damage.
H371	May cause damage to organs .
H361	Suspected of damaging fertility or the unborn child .
EUH208	Contains reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use. Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations. The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.