ProductAcrylic Soft SheenRevision date04 September 2020Revision2



Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking **1.1 Product identifier Acrylic Soft Sheen** Product name Synonyms, Trade names No information available. 1.2 Relevant identified uses of the substance or mixture and uses advised against **Identified uses** This is a waterborne, acrylic resin based paint for interior use on walls and ceilings. It gives a low sheen finish that will withstand normal levels of humidity and can be wiped clean. Uses advised against Any other purpose. **1.3 Details of the supplier of the safety data sheet** Supplier Castle Paints Ltd **Cloncollig Industrial Estate** Tullamore Offaly R35 X993 Ireland Tel: 353 (0)579351583 **Contact person** info@castlepaints.ie **1.4 Emergency telephone number Emergency telephone** Emergency medical information: 8am - 10pm (Seven Days) contact National Poison Center, Beaumont Hospital. Telephone: +353 (0) 18092166

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards Human health Environment Not classified Skin. Sens 1 A- H317 Aquatic Chronic 2 - H411

Warning

2.2 Label elements

Contains

Reaction mass of 2-methyl- 2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one 2-methyl-2H-isothiazol-3-one

Label in accordance with (EC) no. 1272/2008



Signal word

Hazard statements

H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P261 Avoid breathing dust/fume/ gas/mist/vapours/spray.

	 P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/eye protection/face protection. Response P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/ attention. Disposal P501 Dispose of contents/ container to a licensed hazardous waste disposal facility in accordance with all applicable regulations.
EUH statements	EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, and reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
2.3 Other hazards	

None known.

Section 3: Composition/identification	of ingredients
---------------------------------------	----------------

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
titanium dioxide	CAS-No.: 13463-67-7 EC No.: 236-675-5 REACH Reg No.: 01-2119489379-17-0046		10-20%
propane-1,2-diol	CAS-No.: 57-55-6 EC No.: 200-338-0 REACH Reg No.: 01-2119456809-23-0000		1-5%
isobutyric acid, monoester with 2,2,4- trimethylpentane-1,3-diol	CAS-No.: 25265-77-4 EC No.: 246-771-9 REACH Reg No.: 01-2119441305-48-0002		1-5%
Distillates (petroleum), solvent dewaxed heavy paraffinic	CAS-No.: 64742-65-0 EC No.: 265-169-7		0.1-0.9%
docusate sodium	CAS-No.: 577-11-7 EC No.: 209-406-4 REACH Reg No.: 01-2119491296-29-0000	Skin Irrit.2 - H315, Eye Dam. 1 - H318	0.01-0.09%
2-(2-butoxyethoxy)ethanol	CAS-No.: 112-34-5 EC No.: 203-961-6 REACH Reg No.: 01-2119475104-44-XXXX	Eye Irrit.2A - H319	0.01-0.09%
Reaction mass of 2-methyl- 2H- isothiazol-3-one and 5-chloro- 2-methyl-2H-isothiazol-3-one	CAS-No.: 55965-84-9 EC No.:	Acute Tox 3 - H301, Acute Tox 2 - H310, Skin Corr. 1B - H314, Skin. Sens 1 - H317, Acute Tox 3 - H331, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	0.01-0.09%
2-methyl-2H-isothiazol-3-one	CAS-No.: 2682-20-4 EC No.: 220-239-6	Acute Tox 3 - H301, Acute Tox 3 - H311, Skin Corr. 1B - H314, Skin. Sens 1 - H317, Eye Dam. 1 - H318, STOT SE 3 - H335, Aquatic Acute 1 - H400	0.001-0.009%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Distillates (petroleum), solvent-dewaxed heavy paraffinic: This product is not classified as carcinogenic as it complies with note L having polynuclear aromatic hydrocarbon content <3% determined in accordance with IP 346 (dimethylsulphoxide extraction) (Annex VI – Regulation EC 1272/2008).

Section 4: First aid measures

<u>4.1 Description of first aid measures</u>

General information

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if

	symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.
Inhalation	Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort or breathing difficulties develop.
Ingestion	If this product is ingested, remove victim immediately from source of exposure. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position. Never give anything by mouth to an unconscious person. Rinse mouth out and then drink plenty of water. Seek medical attention.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing and shoes and wash before reuse. Wash exposed area with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if irritation develops or persists.
Eye contact	Avoid contaminating unaffected eye. Remove contact lenses if present and easy to do so. Hold eye lids open. Rinse with a gentle stream water for at least 15 minutes. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms noted.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	May cause an allergic skin reaction. Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Prolonged contact may cause redness and/or tearing.

<u>4.3 Indication of any immediate medical attention and special treatment needed</u>

tes to the physician

Section 5: Fire-fighting measures

5.1 Extinguishing media

Extinguishing media Unsuitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Water spray, foam, dry powder or carbon dioxide. None noted.
enouriero ononguionny mouri	
5.2 Special hazards arising from the su	bstance or mixture
Hazardous combustion products	When heated, vapours/gases hazardous to health may be formed. Metal oxides. Oxides of carbon.
Unusual fire & explosion hazards	No unusual fire or explosion hazards noted.
Specific hazards	Do not allow run-off from fire fighting to enter drains or water courses.
5.3 Advice for firefighters	
Special fire fighting procedures	Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires
	from safe distance or protected location. Ventilate closed spaces before entering them.
	Containers close to fire should be removed immediately or cooled with water if safe to do so.
Protective equipment for firefighter	rs Fire-fighters should wear appropriate protective equipment and self-contained breathing
	apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire
	fighters (including helmets, protective boots and gloves) conforming to European standard
	EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

$\underline{6.1}$ Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Eliminate all sources of ignition. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Wash hands after
For emergency responders	use. Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions	
Environmental precautions	Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.
6.3 Methods and material for containme	nt and cleaning up
Spill clean up methods	Ventilate and evacuate the area. Stop leak if possible without risk. Cover drains. Wear appropriate personal protective equipment as specified in Section 8. Absorb spillage with non-combustible, absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.
6.4 Reference to other sections	
Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.
Section 7: Handling and storage	
7.1 Precautions for safe handling	
Handling	Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Do not handle broken packages without protective equipment. Do not use contact lenses. Do not eat, drink or smoke when using the product.
7.2 Conditions for safe storage, includin	g any incompatibilities
Storage precautions	Store in tightly closed original container in a cool, dry and well-ventilated place. Keep upright, locked up and out of reach of children. Store in cool dry areas away from direct sunlight or sources of ignition.
Storage class	Unspecified storage.
7.3 Specific end use(s)	
Specific end use(s) Usage description	The identified uses for this product are detailed in Section 1. Use only according to directions. Replace and tighten cap after use.

Section	8:	Exposure	controls/Personal	protection
0000000	~.	poodro	comtroio, 1 0100mai	proceedion

8.1 Control parameters

Component	STD	TWA (8 Hrs)	STEL (1	l 5mins)	Notes
titanium dioxide	OEL		10 mg/m ³			Total inhalable dust.
titanium dioxide	OEL		4 mg/m ³			Respirable dust.
propane-1,2-diol	OEL	150 ppm	470 mg/m ³			Total (vapour and particulates).
propane-1,2-diol	OEL		10 mg/m ³			Particulates.
Distillates (petroleum), solvent dewaxed heavy paraffinic	OEL		5 mg/m ³			Mineral oil - Pure, Highly & Severely Refined (Inhalable).
2-(2-butoxyethoxy)ethanol	OEL	10 ppm	67.5 mg/m ³	12 ppm	101.2 mg/m ³	IOELV.

Ingredient comments

Ireland, Occupational Exposure Limits 2020.

8.2 Exposure Controls

Protective equipment



Engineering measures	Provide adequate ventilation, including appropriate local extraction, to ensure that the
Respiratory equipment	defined occupational exposure limit is not exceeded. Wear respiratory protection if ventilation is inadequate. Where risk assessment shows air- purifying respirators are appropriate a full face respirator conforming to EN 143 should be used, and suitable respirator cartridges as a backup to engineering controls. Suggested filter type A/P2 (EN 141). ABEK (EN 14387). If the respirator is the sole means of protection, use a full-face supplied air respirator. Consult manufacturer for specific advice. Use respirators and components tested and approved under appropriate government standards such as CEN (EU). Use respiratory protection as specified by an industrial hygienist or other qualified professional if concentrations exceed the limits listed in Section 8.
Hand protection	Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. Gloves must be inspected prior to use. Suggested material: Nitrile rubber. Break through time: >480 minutes. Minimum layer thickness: 0.33 mm. Chloroprene. Breakthrough time: >480 minutes. Minimum layer thickness: 0.6 mm. Consult manufacturer for specific advice.
Eye protection	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).
Other protection	Wear appropriate clothing to prevent skin contact. Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the European norm standard EN 943.
Hygiene measures	Immediately take off any contaminated clothing and launder before re-use. Wash promptly if skin becomes contaminated. Wash hands after handling. Do not eat, drink, or smoke while using this product.
Process conditions	Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Colour Odour	Viscous liquid. Various. Faint.
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	8.00
pH-Value, Diluted solution	No information available as testing has not been completed.
Melting point	No information available as testing has not been completed.
Initial boiling point and boiling range	No information available as testing has not been completed.
Flash point	Not Applicable (product does not support combustion).
Evaporation rate	No information available as testing has not been completed.
Flammability state	The product is not classified as flammable.
Flammability limit - lower(%)	No information available as testing has not been completed.
Flammability limit - upper(%)	No information available as testing has not been completed.
Vapour pressure	No information available as testing has not been completed.

	Vapour density (air=1)	No information available as testing has not been completed.	
	Relative density	1.230g/cm ³ @ 20.00 °C	
	Bulk density	No information available as testing has not been completed.	
	Solubility	Partially soluble in cold water.	
	Decomposition temperature	No information available as testing has not been completed.	
	Partition coefficient; n- Octanol/Water	No information available as testing has not been completed.	
	Auto ignition temperature (°C)	Not applicable.	
	Viscosity	2,500 cP @ 20.00°C (viscous liquid).	
	Explosive properties	Not classified as explosive.	
	Oxidising properties	The product does not meet the criteria to be classified as oxidising.	
9.2 Other information			
	Molecular weight	The product is a mixture, molecular weight data is not required.	
	Volatile organic compound	EU limit for this product (Cat A/a) 30 g/l. This product contains < 30 g/l VOC.	
	Other information	None noted.	

Section 10: Stability and reactivity	
10.1 Reactivity	
Reactivity	Reaction with: strong oxidising substances and acids.
10.2 Chemical stability	
Stability	Stable under normal temperature conditions and recommended use.
10.3 Possibility of hazardous reactions	
Hazardous reactions Hazardous polymerisation Polymerisation description	None under normal processing. No information available as testing has not been completed. No information available as testing has not been completed.
10.4 Conditions to Avoid	
Conditions to avoid	Heat, sparks, open flames, temperature extremes and direct sunlight.
10.5 Incompatible materials	
Materials to avoid	Strong oxidising agents. Strong acids. Do not mix with other chemicals unless listed on directions.
10.6 Hazardous decomposition products	
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Decomposition products may include: Metal oxides.
Section 11: Toxicological information	

11.1 Information on toxicological effects		
Toxicological information	No toxicological information for the overall finished product.	
Acute toxicity (Oral LD50) Acute toxicity (Dermal LD50)	No information available as testing has not been completed. No information available as testing has not been completed.	

Acute toxicity (Inhalation LD50)	No information available as testing has not been completed.	
Serious eye damage/irritation	May cause temporary eye irritation.	
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.	
Respiratory sensitisation Skin sensitisation	The product is not classified as a respiratory hazard. The product is classified as a skin sensitisation hazard.	
Germ cell mutagenicity	The product is not classified as a mutagen.	
Carcinogenicity	The product is not classified as a carcinogen hazard.	
Specific target organ toxicity - Single exposure:STOT - Single exposureThe product is not classified as a single exposure specific target organ toxin.Specific target organ toxicity - Repeated exposure:The product is not classified as a repeat exposure specific target organ toxin.STOT - Repeated exposureThe product is not classified as a repeat exposure specific target organ toxin.		
Inhalation Ingestion Skin contact Eye contact Waste management	No specific symptoms noted. May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause an allergic skin reaction. Prolonged contact may cause redness, irritation and dry skin. Prolonged contact may cause redness and/or tearing. When handling waste, consideration should be made to the safety precautions applying to	
Routes of entry Target organs	handling of the product. Do not pour into drains or waterways. Eye and skin contact, ingestion or inhalation. Skin.	
Aspiration hazards: Reproductive toxicity:	The product is not classified as an aspiration hazard. The product is not classified as a reproductive hazard.	

Name	LD50 oral	LD50 dermal	LD50 inhalation
propane-1,2-diol	22000.00mg/kg Rat	>2000.00mg/kg Rabbit	
docusate sodium	4200.00mg/kg Rat		20.00mg/l (vapours) Rat 4 Hours
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	6500.00mg/kg Rat	15200.00mg/kg Rabbit	
2-(2-butoxyethoxy)ethanol	3305.00mg/kg Rat	2764.00mg/kg Rabbit	
2-methyl-2H-isothiazol-3-one	200.00mg/kg Rat	1/UUU UUma/ka Bat	0.53mg/l (dust/mist) Rat 4 Hours

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrate	s No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.
Chronic toxicity - Aquatic	No information available as testing has not been completed.
invertebrates	
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	Toxic to aquatic life with long lasting effects.
Eco toxilogical information	No ecological toxicity available on the overall finished product.

12.2 Persistence and degradability

Degradability Biological oxygen demand Chemical oxygen demand

No information available as testing has not been completed. No information available as testing has not been completed. No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential

No information available as testing has not been completed.

Bioaccumulation factor Partition coefficient; n-Octanol/Water No information available as testing has not been completed. No information available as testing has not been completed.

12.4 Mobility in soil

Mobility

No information available as testing has not been completed.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.


12.6 Other adverse effects

Other adverse effects None known.

Name		Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
propane-1,2-diol	I Incharbunchile mykies (Rainbow	LC50 48 Hours 18340.00mg/l Daphnia magna	
Isobutyric acid, monoester with 2,2,4- trimethylpentane-1 3-diol	LC0 96 Hours >19.00mg/l Onchorhynchus mykiss (Rainbow Trout)	EC50 48 Hours 147.80mg/l Daphnia magna	
	LC50 96 Hours 1300.00mg/l Lepomis macrochirus (Bluegill)		96 Hours >100.00mg/l Scenedesmus Subspicatus
1,2-benzisothiazol-3(2H)-one	11,C50,96 Hours $(1,74ma/1)$	EC50 48 Hours 2.44mg/l Daphnia magna	

Section 13: Disposal considerations	
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product. Do not pour into drains or waterways.
13.1 Waste treatment methods	
Disposal methods	Dispose of waste and residues in accordance with local authority requirements. Empty containers or liners may retain some product residues. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Section 14: Transport information	
14.1 UN number	
UN no. (ADR)	UN3082
UN no. (IMDG) UN no. (IATA)	UN3082 UN3082
	01/3062
<u>14.2 UN proper shipping name</u>	
ADR proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction mass of 2- methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one + 1,2-benzisothiazo- -3(2H)-one)
IMDG proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction mass of 2- methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one + 1,2-benzisothiazo- -3(2H)-one)
IATA proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (Reaction mass of 2- methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one + 1,2-benzisothiazo- -3(2H)-one)
<u>14.3 Transport hazard class(es)</u>	
ADR class	9
IMDG class	9
IATA class	9

Transport labels



14.4 Packing group

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III
14.5 Environmental hazards	
ADR	Yes
IMDG	Yes
IATA	Yes
14.6 Special precautions for user	
EMS	F-A, S-F
Emergency action code	A97 A158 A197
Hazard no. (ADR)	90
Tunnel restriction code	(E)

14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 830/2015 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Approved code of practice	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
Chemical safety assessment	No chemical safety assessment has been carried out.
Section 16: Other information	
General information Revision comments	 2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019) This Safety Data Sheet is in accordance with REACH Annex II, (EC) No 830/2015. This is a second issue. [1]Information updated. [2]Information updated. Classification updated. [4]Information updated. [3]Information updated. [5]Information updated. [6]Information updated. [7]Information updated. [8]Information updated. Code of practice updated. [9]Information updated. [10]Information updated. [11]Information updated. [12]Information updated. [15]Information updated.
Revision date Supersedes date Revision Safety data sheet status	 [12]Information updated. [13]Information updated. [16]Information updated. 04 September 2020 05 January 2018 2 Approved.
Hazard statements in full	
H315 H319	Causes skin irritation. Causes serious eye irritation.

H412	Harmful to aquatic life with long lasting effects.
H318	Causes serious eye damage.
H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H335	May cause respiratory irritation.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, and reaction mass of 2- methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use. Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations. The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.